



## TECHNICAL DATASHEET

HEATING TORCH ideal for plumbers & installers

MODEL: FKL108



Handgriff

Total length

3 interchangeable burners:

Ø 50 mm - inject Ø 1.10 mm

Ø 35 mm - inject Ø 0.50 mm

Ø 25 mm - inject Ø 0.40 mm

Gas type

Pressure range

Nominal pressure

Net weight

WITH REGULATION TRIGGER

360 mm

Power 43 kW - 3 bar pressure

Power 11 kW - 4 bar pressure

Power 4.60 kW - 4 bar pressure

L.P.G G30-G31

1-7 BAR

2-5 BAR

1.32 Kg

THE HOSE IS IN CONFORMITY WITH EUROPEAN NORM UNI EN ISO 3821 - 100% NBR SBR

Rubber weight

Rubber hose length

Nominal pressure range

Brust pressure

Temperature range

Expiry of the rubber starting from the date of production

0.126 Kg/mt +/- 0.008 Kg/mt

5 mt

0 - 20 BAR

> 60 BAR

- 20° / + 70° C

5 years



INTEGRATED FIXING WRENCHES

ALL PCS ARE INDIVIDUALLY TESTED WITH LPG PRESSURE 4 BAR DVGW HOMOLOGATION N. DG-2212M0077







